



MODULOCK MONO 120

Specifications


| | |
|------------------------------|--------------------------|
| Nominal Power (W) | 120 W |
| Luminous Flux (lm) | 13800 - 16200 lumen |
| Efficacy (lm/W) | 115 - 135 lm/W |
| Nominal Voltage (V) | 220 - 240 V / 50 - 60 Hz |
| Power Factor | > 0.95 |
| IEC Protection Class | Class I |
| Ingress Protection | IP 66 |
| Impact Protection | IK 09 |
| Colour Rendering Index (CRI) | > 70 |
| Colour Temperature (K) | 2700 - 6500 K |
| Operating Temperature (Ta) | Outdoor -20 °C / +50 °C |
| Diffuser | 4 mm Tempered Glass |
| Optic | PMMA |
| Surge Protection (kV) | 6 - 10 kV |
| Control Protocols | 1-10V DALI ZigBee DMX |
| Housing | Die-Cast Aluminum |
| Tilt Angle | -90° / +90° |
| Dimensions and Weight | 360 x 345 x 74 mm / 5 kg |
| Colour Options | All RAL colours |

IP66 IK09 CE ENEC TSC SURE LIGHT VDE RAMS

Description

LED Floodlight

Photometric Distribution:



Complied Standards:

LM 79-08, LM 80
EN 60598-1:2015+A1:2018
EN 60598-2-13:2006+A1:2012+A2:2016
EN 62262:2002
IEC TR 62778:2014

LED Lifetime:

120,000 hours L80

Applications

- Industrial Zones
- Sports Venues
- Parks and Car Lots
- Architectural and Urban
- Bridges and Viaducts
- Residential Areas
- Railway Stations



CORPORATE

Company
Quality and R&D
Certificates
News
Career

PRODUCTS

Road and Street Luminaires
Floodlights and Area Luminaires
Industrial and Tunnel Luminaires
Indoor and Office Luminaires
Poles and Bollards
İMAJ® Ballasts and Ignitors
GRITCON® Smart Control
GRITSOL® Solar Systems

CONTACT US

E-Mail : sales@grupimaj.com
Phone : +90 212 689 93 08-09-10 (pbx)
Fax : +90 212 689 93 11
GSM : +90 507 699 53 32
Address : Kavaklı district, Deniz Aktaş street, No: 6 |
345520 Beylikdüzü / İstanbul / TÜRKİYE