



MODULOCK PENTA 750

Specifications


Nominal Power (W)	750 W
Luminous Flux (lm)	86250 - 101250 lumen
Efficacy (lm/W)	115 - 135 lm/W
Nominal Voltage (V)	220 - 240 V / 50 - 60 Hz
Power Factor	> 0.95
IEC Protection Class	Class I
Ingress Protection	IP 66
Impact Protection	IK 09
Colour Rendering Index (CRI)	> 70
Colour Temperature (K)	2700 - 6500 K
Operating Temperature (Ta)	Outdoor -20 °C / +50 °C
Diffuser	4 mm Tempered Glass
Optic	PMMA
Surge Protection (kV)	6 - 10 kV
Control Protocols	1-10V DALI ZigBee DMX
Housing	Die-Cast Aluminum
Tilt Angle	-90° / +90°
Dimensions and Weight	970 x 625 x 74 mm / 24 kg
Colour Options	All RAL colours

IP66 IK09 CE ENEC TSC TÜRKELİTİM VDE RAMS

Description

LED Industrial and Tunnel Lighting Luminaire

Photometric Distribution:



Complied Standards:

LM 79-08, LM 80
EN 60598-1:2015+A1:2018
EN 60598-2-13:2006+A1:2012+A2:2016
EN 62262:2002
IEC TR 62778:2014

LED Lifetime:

120,000 hours L80

Applications

- Tunnel and Underpass
- Industrial Zones
- Parks and Car Lots
- Architectural and Urban
- Railway Stations



CORPORATE

Company
Quality and R&D
Certificates
News
Career

PRODUCTS

Road and Street Luminaires
Floodlights and Area Luminaires
Industrial and Tunnel Luminaires
Indoor and Office Luminaires
Poles and Bollards
İMAJ® Ballasts and Ignitors
GRITCON® Smart Control
GRITSOL® Solar Systems

CONTACT US

E-Mail : sales@grupimaj.com
Phone : +90 212 689 93 08-09-10 (pbx)
Fax : +90 212 689 93 11
GSM : +90 507 699 53 32
Address : Kavaklı district, Deniz Aktaş street, No: 6 |
345520 Beylikdüzü / İstanbul / TÜRKİYE