



## NELO 60 - R 25

### Specifications


Nominal Power (W)	25 W
Luminous Flux (lm)	2500 - 3125 lumen
Efficacy (lm/W)	100 - 125 lm/W
Nominal Voltage (V)	220 - 240 V / 50 - 60 Hz
Power Factor	> 0.95
IEC Protection Class	Class I
Ingress Protection	IP 40
Impact Protection	IK 06
Colour Rendering Index (CRI)	> 80
Colour Temperature (K)	3000 - 4000 K
Operating Temperature (Ta)	-20 °C / +50 °C
Diffuser	PMMA
Optic	PMMA
Control Protocols	1-10V DALI ZigBee DMX
Housing	Galvanize
Dimensions and Weight	595 x 595 x 60 mm / 2.8 kg
Colour Options	RAL 9005, 9006, 9016



### Description

LED Indoor and Office Luminaire

*Photometric Distribution:*



*Complied Standards:*

LM 79-08, LM 80  
EN 60598-1:2015+A1:2018  
EN 60598-2-13:2006+A1:2012+A2:2016  
EN 62262:2002  
IEC TR 62778:2014

*LED Lifetime:*

120,000 hours L80

### Applications

- Offices and Plaza
- Restaurants and Malls
- Hotels and Residences
- Hospitals and Schools
- Airports
- Railway Stations



#### CORPORATE

Company  
Quality and R&D  
Certificates  
News  
Career

#### PRODUCTS

Road and Street Luminaires  
Floodlights and Area Luminaires  
Industrial and Tunnel Luminaires  
Indoor and Office Luminaires  
Poles and Bollards  
IMAJ® Ballasts and Ignitors  
GRITCON® Smart Control  
GRITSOL® Solar Systems

#### CONTACT US

E-Mail : sales@grupimaj.com  
Phone : +90 212 689 93 08-09-10 (pbx)  
Fax : +90 212 689 93 11  
GSM : +90 507 699 53 32  
Address : Kavaklı district, Deniz Aktaş street, No: 6 |  
345520 Beylikdüzü / Istanbul / Turkey

