



PS 150

Specifications


Nominal Power (W)	150 W
Luminous Flux (lm)	10500 - 15000 lumen
Efficacy (lm/W)	70 - 100 lm/W
Nominal Voltage (V)	220 - 240 V / 50 - 60 Hz
IEC Protection Class	Class I
Lamp Holder	E40
Ingress Protection	IP 65
Impact Protection	IK 08
Colour Rendering Index (CRI)	> 25
Colour Temperature (K)	2000 K
Operating Temperature (Ta)	Outdoor -20 °C / +50 °C
Diffuser	4 mm Tempered Glass
Optic	Aluminum Reflector
Housing	Polymer
Mounting Part	Die-Cast Aluminum
Tilt Angle	-90° / +90°
Dimensions and Weight	550 x 426 x 165 mm / 4 kg

IK08 CE   IP65 

Description

Floodlight

Photometric Distribution:



Complied Standards:

LM 79-08, LM 80
EN 60598-1:2015+A1:2018
EN 60598-2-13:2006+A1:2012+A2:2016
EN 62262:2002
IEC TR 62778:2014

Applications

- Industrial Zones
- Sports Venues
- Parks and Car Lots
- Architectural and Urban
- Bridges and Viaducts
- Residential Areas
- Railway Stations



CORPORATE

Company
Quality and R&D
Certificates
News
Career

PRODUCTS

Road and Street Luminaires
Floodlights and Area Luminaires
Industrial and Tunnel Luminaires
Indoor and Office Luminaires
Poles and Bollards
IMAJ® Ballasts and Ignitors
GRITCON® Smart Control
GRITSOL® Solar Systems

CONTACT US

E-Mail : sales@grupimaj.com
Phone : +90 212 689 93 08-09-10 (pbx)
Fax : +90 212 689 93 11
GSM : +90 507 699 53 32
Address : Kavaklı district, Deniz Aktaş street, No: 6 |
345520 Beylikdüzü / İstanbul / TÜRKİYE

