



SITA 2

Specifications

Nominal Power (W)	2 W
Luminous Flux (lm)	120 - 150 lumen
Efficacy (lm/W)	100 - 125 lm/W
Nominal Voltage (V)	220 - 240 V / 50 - 60 Hz
Power Factor	> 0.95
IEC Protection Class	Class II
Ingress Protection	IP 20
Impact Protection	IK 06
Colour Rendering Index (CRI)	> 80
Colour Temperature (K)	3000 - 4000 K
Operating Temperature (Ta)	-5 °C / +40 °C
Diffuser	PMMA
Optic	PMMA
Housing	ABS
Dimensions and Weight	254 x 150mm / 0,45 kg



Description

LED Indoor and Office Luminaire

Complied Standards:

LM 79-08, LM 80
EN 60598-1:2015+A1:2018
EN 60598-2-13:2006+A1:2012+A2:2016
EN 62262:2002
IEC TR 62778:2014

LED Lifetime:

120,000 hours L80

Applications

- Offices and Plaza
- Restaurants and Malls
- Hotels and Residences
- Hospitals and Schools
- Airports
- Railway Stations



CORPORATE

Company
Quality and R&D
Certificates
News
Career

PRODUCTS

Road and Street Luminaires
Floodlights and Area Luminaires
Industrial and Tunnel Luminaires
Indoor and Office Luminaires
Poles and Bollards
IMAJ® Ballasts and Ignitors
GRITCON® Smart Control
GRITSOL® Solar Systems

CONTACT US

E-Mail : sales@grupimaj.com
Phone : +90 212 689 93 08-09-10 (pbx)
Fax : +90 212 689 93 11
GSM : +90 507 699 53 32
Address : Kavaklı district, Deniz Aktaş street, No: 6 |
345520 Beylikdüzü / Istanbul / Turkey