



TIAN 40

Specifications


| | |
|------------------------------|----------------------------|
| Nominal Power (W) | 40 W |
| Luminous Flux (lm) | 4000 - 5000 lumen |
| Efficacy (lm/W) | 100 - 125 lm/W |
| Nominal Voltage (V) | 220 - 240 V / 50 - 60 Hz |
| Power Factor | > 0.95 |
| IEC Protection Class | Class I |
| Ingress Protection | IP 40 |
| Impact Protection | IK 06 |
| Colour Rendering Index (CRI) | > 80 |
| Colour Temperature (K) | 3000 - 4000 K |
| Operating Temperature (Ta) | -20 °C / +40 °C |
| Diffuser | Policarbon |
| Optic | PMMA |
| Control Protocols | 1-10V DALI ZigBee DMX |
| Housing | Aluminum |
| Dimensions and Weight | 1680 x 67 x 43 mm / 1,5 kg |
| Colour Options | RAL 9005, 9006, 9016 |



Description

LED Indoor and Office Luminaire

Photometric Distribution:



Complied Standards:

LM 79-08, LM 80
 EN 60598-1:2015+A1:2018
 EN 60598-2-13:2006+A1:2012+A2:2016
 EN 62262:2002
 IEC TR 62778:2014

LED Lifetime:
 120,000 hours L80

Applications

- Offices and Plaza
- Restaurants and Malls
- Hotels and Residences
- Hospitals and Schools
- Airports
- Railway Stations

