

TP 150 Home > Products > TP 150



### TP 150

### Specifications

Nominal Power (W)	150 W
Luminous Flux (Im)	10500 - 15000 lumen
Efficacy (Im/W)	70 - 100 lm/W
Nominal Voltage (V)	220 - 240 V / 50 - 60 Hz
Ingress Protection	IP 65
Impact Protection	IK 08
Lamp Holder	E40
IEC Protection Class	Class I
Colour Temperature (K)	2000 K
Colour Rendering Index (CRI)	> 25
Operating Temperature (Ta)	Outdoor -20 °C / +50 °C
Diffuser	Policarbon
Optic	Aluminum Reflector
Housing	Polymer
Mounting Part	Die-Cast Aluminum
Mounting Diameters	Ø42 mm - Ø60 mm
Tilt Angle	-15° / +15°
Dimensions and Weight	664 x 324 x 200 mm / 6.1 kg













## Description

Street Lighting Luminaire

#### Photometric Distribution:



Complied Standards: Approved by Turkish General Directorate of Highways EN 60598-1:2015+A1:2018 EN 60598-2-13:2006+A1:2012+A2:2016 FN 62262:2002 IEC TR 62778:2014

# Applications

- · Streets and Roads
- · Parks and Car Lots
- · Residential Areas
- Industrial Zones
- Railway Stations





### CORPORATE

Quality and R&D Certificates News Career

### PRODUCTS

Road and Street Luminaires Floodlights and Area Luminaires Industrial and Tunnel Luminaires Indoor and Office Luminaires Poles and Bollards IMAJ® Ballasts and Ignitors GRITCON® Smart Control GRITSOL® Solar Systems

### CONTACT US

E-Mail : sales@grupimaj.com Phone : +90 212 689 93 08-09-10 (pbx) Fax: +90 212 689 93 11 GSM: +90 507 699 53 32 Address : Kavaklı district, Deniz Aktaş street, No: 6 | 345520 Beylikdüzü / Istanbul / Turkey







