



## TS 100

### Specifications


Nominal Power (W)	100 W
Luminous Flux (lm)	7000 - 10000 lumen
Efficacy (lm/W)	70 - 100 lm/W
Nominal Voltage (V)	220 - 240 V / 50 - 60 Hz
Ingress Protection	IP 65
Impact Protection	IK 08
Lamp Holder	E40
IEC Protection Class	Class I
Colour Temperature (K)	2000 K
Colour Rendering Index (CRI)	> 25
Operating Temperature (Ta)	Outdoor -20 °C / +50 °C
Diffuser	4 mm Tempered Glass
Optic	Aluminum Reflector
Housing	Polymer
Mounting Part	Die-Cast Aluminum
Mounting Diameters	Ø42 mm - Ø60 mm
Tilt Angle	-15° / +15°
Dimensions and Weight	664 x 324 x 149mm / 5.6 kg



### Description

Street Lighting Luminaire

*Photometric Distribution:*



*Complied Standards:*

Approved by Turkish General Directorate of Highways  
EN 60598-1:2015+A1:2018  
EN 60598-2-13:2006+A1:2012+A2:2016  
EN 62262:2002  
IEC TR 62778:2014

### Applications

- Streets and Roads
- Parks and Car Lots
- Residential Areas
- Industrial Zones
- Railway Stations



#### CORPORATE

Company  
Quality and R&D  
Certificates  
News  
Career

#### PRODUCTS

Road and Street Luminaires  
Floodlights and Area Luminaires  
Industrial and Tunnel Luminaires  
Indoor and Office Luminaires  
Poles and Bollards  
IMAJ® Ballasts and Igniters  
GRITCON® Smart Control  
GRITSOL® Solar Systems

#### CONTACT US

E-Mail : sales@grupimaj.com  
Phone : +90 212 689 93 08-09-10 (pbx)  
Fax : +90 212 689 93 11  
GSM : +90 507 699 53 32  
Address : Kavaklı district, Deniz Aktaş street, No: 6 |  
345520 Beylikdüzü / Istanbul / Turkey

